

Dynacom DN6432F , 32ch NVR, 4*SATA



- H.265 video compression
- Third-party IP cameras supported with ONVIF conformance
- Support PnP for easy IPC discovery and usage
- Up to 8 Megapixels resolution recording, storage and playback
- Support 2-ch HDMI, 1-ch VGA, HDMI2 is up to 4K(3840x2160) resolution
- Up to 16 channels synchronously playback
- Support instant playback
- Support corridor mode
- 4 SATA HDDs up to 24TB

Model No.	DN6432F
Video/Audio Input	
IP Video Input	32 CH
Two-way Audio Input	1 CH, RCA (2.0 Vp-p, 1kΩ)
Network	
Incoming bandwidth	320Mbps
Outgoing bandwidth	320Mbps
Remote connection	16
Network Protocols	IPv4/IPv6, TCP/IP, HTTP, UPNP, RTSP, UDP, SMTP, NTP, FTP, DHCP, DNS, DDNS, PPPoE, DDNS
Video/Audio Output	
HDMI Output	2
VGA Output	1
CVBS Output	/
Audio Output	1 CH, RCA
Decoding	
Live View/Playback Resolution	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/VGA/D1/CIF
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/VGA/D1/CIF
Synchronous Playback	16 CH 32 x 720P@25, 16 x 720P@30, 16 x 1080P@25, 7 x 4MP@30, 5 x 5MP@30, 4 x 6MP@30, 4 x 4K@25
Hard Disk	
SATA	4
Capacity	Up to 6TB for each disk
External Interface	
Network Interface	2RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
Serial Interface	1 RS-232, 1 RS-485
USB Interface	2 USB2.0 + 1 USB3.0
eSATA Interface	/
Alarm In	16
Alarm Out	4
POE	
Interface	NA
Max. Power	/
Supported Standard	NA
General	
Power Supply	12V, DC
Consumption	≤12W (Without Disk)
Working Temperature	-10°C ~ 55°C (14°F ~ 131°F)
Working Humidity	10% ~ 90%
Dimensions	44.0mm × 440.0mm × 344.0mm (1.73" × 17.32" × 13.54"), 1U
Weight(without HDD)	≤3.2KG

