

Dynacom WQ820A / WQ820AP Outdoor IR Bullet IP Camera



- 1/2.8" 2M SONY Exmor CMOS Sensor
- 2 Megapixel
- 0Lux
- 10M(2pcs IR Array)
- 3.6mm Lens
- Color to BW:2Lux; BW to Color:6Lux
- DC 12V / PON(power by NVR mainboard)
- PoE (Power Over Ethernet) for only WQ820AP
- IP66

| | |
|-----------------------|--|
| Model No. | WQ820A / WQ820AP |
| PARAMETER | |
| Image Sensor | 1/2.8" 2MP Sony Exmor CMOS Sensor |
| Pixels | 1920(H)x1080(V) |
| Minimum illumination | 0Lux |
| S/N | ≥45db |
| IR | >10M(2pcs IR Array) |
| IR-Cut | Color to BW:2Lux; BW to Color:6Lux |
| OPTICAL LENS | |
| Interface | M12 |
| Lens | Fixed Iris Lens |
| Focal length | 3.6mm |
| NETWORK | |
| Network interface | RJ45 10M/100M |
| Network Protocol | HTTP,TCP,ARP,RTSP,RTP,UDP,RTCP,SMTP,FTP,DHCP,DNS,DDNS,PPPoE,IPv4/v6,SNMP,QoS,UPnP,NTP |
| ONVIF | Supports |
| Network Preview | Web server embedded, Support IE |
| VIDEO | |
| Video encode | H.264 Baseline Profile/H.264 Main Profile |
| Resolution | Main stream:1080p @ 30fps; Sub stream:540P(960*540)@ 30fps/VGA/1080P @ 1fps for snapshot |
| Bitrate | 512Kbps~8Mbps |
| CBR/VBR | Support |
| Local Storage | SD card (up to 64GB) |
| OTHERS | |
| Operation Temperature | -10°C-- + 55°C |
| Operation Humidity | 0% - 90% |
| Power supply | DC 12V / PON(power by NVR mainboard) /PoE (Power Over Ethernet) for only WQ820AP |
| Protection | IP66 |
| Power | <5w |
| Dimension | unfolded: Φ60*151.3MM; fold: Φ60*113.2MM |



2MP

