

# Dynacom WQ830AZ Outdoor IR Motorized Bullet IP Camera



- 1/2.8" 2M SONY Exmor CMOS Sensor
- H.264 Encoding, Max Resolution 1920\*1080
- 80db D-WDR, 2D/3D DNR, Motion Detection, PSW, P2P
- Support Automatic IR-CUT
- Support Windows Mobile、iPhone、iPad、Android Platform
- 30m IR Range
- Input Voltage: DC12V(POE)

Model No.	WQ830AZ
<b>CAMERA</b>	
Sensor	1/2.8" 2MP Sony Exmor CMOS Sensor
Min Illumination	0.01Lux@F1.2 (0Lux,IR on)
S/N	≥50dB(AGC OFF)
WDR	≥80dB
IR LEDs	4 pcs IR Array
IR Range	80m
Lens	Motorized 2.8-12mm Auto Iris
Current	1200mA
Power Consumption	<15W
Weight	450g
IP Rating	IP66
<b>INTERFACE</b>	
Ethernet	RJ45 10M/100M
Audio Input	1CH Audio Linear Input
<b>VIDEO ENCODE</b>	
Encoding	H.264, Main Profile, MJPEG
Resolution(Main Stream)	1920*1080, 1-25(30)fps
Resolution(Sub Stream)	540P(960*540)@ 30fps/VGA/1080P @ 1fps for snapshot
Video Compression	3512Kbps~8Mbps Continuously adjustable, Support CBR/VBR
Subtitle Overlay	Support Channel Name, Date&Time,Stream Information Overlay,Overlay Position adjustable
<b>DATA TRANSFER AND STORAGE</b>	
Data Storage	Video, Image
Storage Mechanism	Manual, Auto(Loop, Timing,Alarm Switch Input, Motion Detection)
Alarm Data Transfer	FTP, E-mail, Brower, Management Software
Network Protocol	HTTP,TCP,ARP,RTSP,RTP,UDP,RTCP,SMTP,FTP,DHCP,DNS,DDNS,PPPoE,IPv4/v6,SNMP, QoS,UPnP,NTP
Client-Side Browse	IE,firefox,google chrome
ONVIF Protocol	ONVIF 2.4
<b>GENERAL PARAMETERS</b>	
Input Voltage	DC12V±10%/POE
Working Temperature	-10°C~+50°C
Working Humidity	<90%RH(No Condensation)

