

Dynacom DN5132 , 32ch NVR, 8*SATA



- Embedded Linux
- Video compression, H.264
- Video output, CVBS/VGA/HDMI
- Audio in, Audio out
- Alarm 16 in/1 out
- ONVIF

Model No.	DN5132
SYSTEM	
User Interface	Graphic User interface(OSD Menu)
OS	Embedded Linux
ONVIF	Support
Security	Administrator; Different authority for users
VIDEO	
Video input	32 CH 1080P IPC(by switch)
Video output	CVBS/VGA/HDMI
Display	1/4/8/910/13/16 optional
VGA	1024*768,1280*1024,1440*900,1366*768,720P,1080P
Video encoding resolution	PAL:720P(1280X720); 1080P(1920*1080) / NTSC:720P(1280X720); 1080P(1920*1080)
Video frame rate	PAL: 1-25FPS NTSC:1-30FPS
AUDIO	
Audio compress	ADPCM
Audio in	IPC with audio
Audio out	1 out RCA
IMAGE & STORAGE	
Video compress	H.264
Image quality	1080P
Sub stream	Sub stream1:VGA/QVGA; Sub stream2:540P
Resolution	16CH 1080P recording & 4CH realtime playback/8CH playback(22FPS);
Video Bit Rate	720P:1536kbps-3072kbps;1080P:2048-8192kbps
Audio Bit Rate	8-32Kbps
Alarm	
Alarm in/out	16 in/1 out
Others	
Recording	Manual/alarm/motion detection/timing
Network	RJ45 1000M Protocol: TCP/IP, PPPoE, SMTP,UPNP,DHCP and DDNS
Voice talk	Support
Control Method	Remote control, USB mouse, panel control
Mobile live view	iPhone /iPad/Android/Blackberry
Domain name server	Support 88110,reelink,3322, dyndns, no-ip, changeip, dnsexit domain name server as default value.
Backup	USB2.0, Network
Serial	RS485
Power Supply	NVR DC 12V 5A IPC DC 12V 2A
Working Environment	Working temperature: -10°C~+60°C; Working humid:10%~ 90%
Device Dimension	405mm(W)×321mm(D)×55mm(H)
Weight	≤3Kg

