

DYNI-8910-10P

8 port 10/100/1000 PoE + 2 port 100/1000 SFP L2+ Managed Industrial Switch



- 8 Port 1000BaseT
- 2 Port 100/1000 SFP
- L2+ Features
- Total PoE Budget: 240 W
- 8 ports PoE
- IEEE802.1x
- IEEE802.3az
- IEEE802.3z/ab
- IP30
- DIN Rail

Technical Specs.

Model No	DYNI-8910-10P
Port Capacity	10 Port Gigabit Industrial Managed PoE Switch
Port Types	8x 10/100/1000Base-T RJ45 copper ports (PoE) + 2x 100/1000 SFP ports + 1 RJ45 console port

Performance

Switching Capacity	20 Gbps , wire speed (non-blocking)
Forwarding Rate	14.88 Mpps
MAC Table	8K
Jumbo Frames	9.6K
Memory	4M
Auto-negotiation	•
Auto MDI/MDIX	•
Store-and-Forward	•

Layer 2+ Features

Spanning Tree Protocol (STP)	IEEE802.1d Spanning Tree Protocol IEEE802.1w Rapid Spanning Tree Protocol IEEE802.1s Multiple Spanning Tree Protocol Loop Back Detection
IGMP Snooping	IGMP v1/v2
VLANs	Support up to 4K VLANs Port-based VLAN 802.1Q tag-based VLAN
Link Aggregation	IEEE 802.3ad LACP
Ethernet Ring Protection Switching	G.8032 ERPS
Flow Control	IEEE802.3x
Private VLAN	•
Static Routing	•
Q in Q	•

Security Features

<p>Broadcast, multicast , unicast storm control Secure Sockets Layer (SSL), Web security DHCP Snooping ARP Inspection IP Source Guard AAA, RADIUS and TACACS+</p>	<p>Secure Shell (SSH), Telnet security, supports SSH v1 and v2 ACL, VLAN ID or IP address, MAC Based, Protocol based, Port Based, TCP/ UDP Ethernet type, ICMP, IGMP, TCP flag Port Security</p>
--	---

Management

Web/SSL	SNMP (v1, v2, v3)	Firmware upgrade, (HTTP/HTTPs and TFTP)
Port Mirroring	DHCP Client	LLDP
Port Isolation	Web GUI Interface	SNTP
Telnet/SSH	Cable Diagnostics	TFTP
Ping	CPU Load	Syslog
HTTP/HTTPs	Dual Image	
Timezone	RMON	

IPv6

IPv6 MLD snooping	IPv4/IPv6 Dual Protocol Stack
IPv6 Ping	

Quality of Service

CoS	8 queues per port TCP/ UDP Strict priority Weighted Round Robin (WRR)
Rate Limiting	Ingress/Egress Rate control
Traffic classification	IEEE802.1p DSCP / IP precedence

PoE

Standard	IEEE802.3af IEEE802.3at
Total Power Budget	240W
Max. PoE Power for each port	30W

Environment

DC Power Input	47-55V
Total Power Consumption	255W
Operating/Storage Temperature	-40 - 75 °C / -50 - 85 °C
Operating Humidity	5% - 95% , non-condensing

Mechanical

Dimension	165 x 148 x 54 mm
Weight	0.9 kg
Installation	IP30 rating , DIN-rail

Standards

EN55022	EN61000-6-2	EN61000-4-5	IEC60068-2-27 Ea
EN61000-6-4	EN61000-4-2	EN61000-4-6	CE
EN61000-3-2	EN61000-4-3	EN61000-4-8	FCC
EN61000-3-3	EN61000-4-4	IEC60068-2-6	ISO 9001

Ordering Information

DYNI-8910-10P 8 port 10/100/1000 PoE + 2 port 100/1000 SFP L2+ Managed Industrial Switch

Modules

DYNI-MLX2 Industrial Dual Core LX SM 10Km SFP Module -40/75°C

DYNI-MSX2 Industrial Dual Core SX MM SFP Module -40/75°C

*more module ranges are available upon request.