





- 4 Megapixel full HD real time
- Highest resolution 2592\*1520
- 8pcs \* ⊄ 10mm IR Led
- IR Range 20mt
- 2.8 -12mm Lens
- H.264 Compression
- Support Dual-Stream
- Support ONVIF protocol
- Support RTSP browse video in real time

Model No.	WQ4NM
CAMERA	
Sensor / Resolution	1.3" OV / 2592*1520
Min. illumination	0.1Lux @ F1.2 (Color) (0 Lux IR LED On)
Lens	2.8-12mm Lens
Video Output	Main stream:2592*1520
	Deputy stream:704*576
Compression	H.264 Video Code, Support dual-stream
IR Distance	20mt ( 8 pcs )
Bit Rate (CBR/VBR)	Support 32k-8m adjustable,1-30 fps frame rate adjustable
Multi- Streaming	User setting of Stream 1/2 at supported Resolutions
Gain control	Auto
Text Overlay	Time / Date / Camera / Custom OSD
Network Port	One RJ45 Ethernet interface, 10M/100M self-adaption
Standard protocol	Onvif 2.4
Network Protocols	TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP/Onvif
SD Card	Max. 64 GB
3GWireless Transmission	NO
WIFI Wireless Transmission	NO
Mobile phone monitor	Support mobile phone monitor ( Iphone, Windows Mobile, Android)
Operation	Support Web setting,OSD,real-time video transmission,support motive detection and IO alarm linkage for front end shortage/Capture/playback/download
Function	Support Central remind and image linkage after motive detection and IO alarm linkage, support MJPEG capture, Support unit clint-side romote management software Easy7 platform system apply
Audio	Support
Alarm	Optional
Power Supply	DC9V~12V,<3W
Working Temperature	-35°C∼65°C
Protection Rate	ESD 1kv
· · · · · · · · · · · · · · · · · · ·	



WDR



4 MP





