

Dynacom DN5116P 16ch PoE NVR



- Friendly GUI, 21 Languages Built-in
- Free CMS, P2P, QR code Scan Access
- Built-in web interface to support remote client setting and DVR operation
- Patent HDD Management Technology
- Onvif 2.4 Supported
- RS485 and 2 USB2.0 ports

Model No.	DN5116P
SYSTEM	
User Interface	Graphic User interface(OSD Menu)
OS	Embedded Linux
ONVIF	Support
Security	Administrator; Different authority for users
Video input	16 * 720P/8*1080P/4*2K/3MP/4MP IPC(by switch)
Video output	CVBS/VGA/HDMI
Display	1/4/6/8/9/10/13/16 optional
VGA	1024*768,1280*1024,1440*900,1366*768,720P,1080P
Video encoding resolution	PAL:720P(1280X720); 1080P(1920*1080) / NTSC:720P(1280X720); 1080P(1920*1080)
Video frame rate	PAL: 1-25FPS NTSC:1-30FPS
AUDIO	
Audio compress	ADPCM
Audio in	IPC with audio
Audio out	1 out RCA
IMAGE & STORAGE	
Video compress	H.264
Image quality	720P
Sub stream	Sub stream1:VGA/QVGA; Sub stream2:720P
Resolution	16CH 720P recording & 4CH realtime playback;8CH 1080P recording & 2CH realtime playback;4 CH 4MP Recroding &1 CH realtime Playback
Video Bit Rate	WCIF(CIF):512-1024kbps,Wd1(D1):1024-2048bps,720P:1536-3072Kbps,1080P:4608-6144Kbps
Audio Bit Rate	8-32Kbps
Storage	2 HDD
ALARM	
Alarm in/out	8 in/1 out
OTHERS	
Recording	Manual/alarm/motion detection/timing
Network	RJ45 1000M Protocol: TCP/IP, PPPoE, SMTP,UPNP,DHCP,DDNS,RTSP
Voice talk	Support
Control Method	Remote control, USB mouse, panel control
Mobile live view	I phone //IPAD/Android
Domain name server	Support viewcan 88110,reelink,3322, dyndns, no-ip, changeip, dnsexit domain name server as default value.
Backup	USB2.0, Network
Serial	RS485
POWER SUPPLY	
NVR	DC 12V 5A
IPC	DC 12V 2A
Working Environment	Working temperature: -10°C~+60°C; Working humid:10%~ 90%
Device Dimension	2HDD case:321mm(W)×405mm(D)×64mm(H)
Weight	2HDD case:≤3Kg

