

Dynacom WQ55ZAI **STARVIS IP Dome Camera**

1/2.8" STARVIS progressive scan CMOS Sensor

Max. 5MP(2592×1944) @25/30fps resolution

2.7~13.5mm motorized lens

True WDR 120dB,

3D DNR, ROI, HLC, BLC, Defog

Support face, human, vehicle detection and capture

Intelligent detection: Perimeter, Single virtual fence, Double virtual fences, Loiter, Converse, People counting


1/1 audio in/out, 1/1 alarm in/out

Smart IR up to 40m

Built-in micro SD slot 256GB, IP66, IK10, PoE



Dimensions



Camera	
Image Sensor	1/2.8" STARVIS Progressive Scan CMOS
Effective Pixels	2592(H)×1944(V)
Electronic Shutter	Auto/Manual, 1/5 ~ 1/20,000s
Min. illumination	Color: 0.03 Lux @ (F1.6, AGC ON), B/W: 0 Lux @ (IR LED ON)
S/N Ratio	55dB
Day/Night	Auto(ICR)/Day/Night/Time
Wide Dynamic Range	True WDR 120dB
IR Range	Up to 40 m (131.2 ft)
IR On/Off Control	Auto/Manual
Pan/Tilt/Rotation Range	Pan: 0° ~ 355°, Tilt: 0° ~ 80°, Rotation: 0° ~ 355°
Lens	
Lens Type	Motorized focus
Iris	Fixed Iris
Focal Length	2.7 ~ 13.5 mm
F Number	F1.6
Angle of View	H: 95.5°~26.9°, V: 65.4°~20.5°
Video	
Max. Resolution	5MP (2592×1944)
Streaming Capability	3 Streams
Stream/Frame Rate	Stream1: 2592×1944, 2592×1520, 1920×1080, 1280×720 @ 25/30fps
	Stream2: D1, VGA, CIF @ 25/30fps
	Stream3: VGA, CIF, QVGA @ 25/30fps
Bit Rate Control	CBR/VBR
Bit Rate	Stream1: 200kbps~12Mbps
	Stream2: 100kbps~6Mbps
	Stream3: 100kbps~3Mbps
Image Enhancement	HLC / BLC / Defog / WDR
White Balance	Auto
Gain Control	Auto/Manual
Noise Reduction	2D/3D DNR
Aisle Mode	Support
Smart IR	Support
Mirror	Support
Region of Interest	Off/On (8 Zone, Rectangle)
Motion Detection	Support
Privacy Masking	Support

Smart Function	
Smart Function	Support face, human, vehicle detection and capture
Intelligent Detection	Perimeter, Single Virtual Fence, Double Virtual Fences, Loiter, People Counting
Audio	
Compression	G.711, RAW_PCM
Bit Rate	8kbps, 16kps, 64kbps
Network	
Protocols	IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ARP, SNMP, TLS/SSL
Interoperability	ONVIF, SDK, CGI
Streaming Method	Unicast
Max. User Access	10 Users
Web Viewer	<IE11, Chrome, Firefox, Microsoft Edge
Interface	
Network Interface	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio Interface	1ch Input, 1ch Output
Alarm Interface	1ch Input, 1ch Output
Reset Button	Support
Built-in Micro SD slot	Yes, up to 256G
Electrical	
Power Supply	DC12V/POE (IEEE 802.3af)
Power Consumption	Max 8.5 W
Operating Temperature	-40°C ~ 55°C (-40°F ~ 131°F)
Operating Humidity	Less than 90% RH
Ingress Protection	IP66, IK10
Certifications	CE/FCC
Casing	Metal
Dimensions	φ130 × 112mm (φ5.12" × 4.41")
Net Weight	0.81 kg (1.79 lb)