

Dynacom WQ920ZV 2.1M IR LED Bullet Camera



- 2Mpixelfullreal time optional
- Highest resolution 1920*1080
- IR Leds:42pcs* 5mm, IR Range: 40M
- 2.8-12mm Motorized Lens
- Built-in IR-CUT, Low power consumption
- H.264 Video Coding
- Support Dual-Stream / ONVIF agreement / RTSP browse video in

Functions

defog : get higher image contrast by filtering , better depth of field , clearer picture

multi-stream technology : Front device can output a variety of different streams to different devices for viewing

Model No.	WQ920ZV
CAMERA	
Sensor	1/ 2.8" Sony Progressive scan CMOS Min.
Illumination	Color 0.1Lux/F1.2; B/W 0.00Lux/F1.2
Electronic Shutter	Auto/Manual (1/25~1/10000)
Day/Night	True Day / Night with ICR Filter.
Video Parameter	DWDR, Mirror, 3D Noise reduction, Sharpness/Lightness adjustable
IR Distance	40M(42xIR III LEDs)
Lens	2.8-12mm Motorized megapixel lens
Lens Interface Type	M12
AUDIO/VIDEO COMPRESSION	
Video Compression	H.264 Video Code. Support dual-stream
Encoding	Dual-stream; Main stream: 1920x1080 25fps/30fps Sub Stream: 720x576 25fps/720x480 30fps
Effective Pixels	1920x1080
Encoding System	Constant bit rate, Variable bit rate optional
Video Bit Rate	Support 32k-16m adjustable,1-30 fps frame rate adjustable
Stream Type	Complex stream/Video stream
Audio Compression	G.711A, G.711U, G.726
Recording	SD Card (up to 64GB)
NETWORK FUNCTION	
Motion Detection	Can set a single detection zone, multi-level sensitivity can be set
Video Mask	Support 4 areas to mask
Screen Capture	Support JPEG format, max. resolution based on encoding resolution
Password Protection	Supported
Character Display	Supported (Channel name, Date)
Alarm Function	Video loss, Network disconnect, Tampering alarm, Storage exception
Mobile Surveillance	Apple iOS, Android
Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP/Onvif
Port Protocol	ONVIF
INTERFACE	
Audio	Line in / Line out
Network Interface	RJ45 10M/100M adaptive
GENERAL	
Operating Conditions	-30°C ~ 55°C/0%~90%
IP Grade	IP66
Power Supply	DC12V /PoE optional
Power Consumption	<5W (without IR LED)
Dimensions	Ø 90 x 270 mm (Ø 3.3 x 7.6 in.) w/ Sunshield
Weight	About 940g



WDR



2MP



Mobile phone monitor
(Android/iPhone
/Windows Mobile)