

Portable Digital Video Recorder RM620



- HD screen

2.4" TFT, resolution:480*240, Image is exquisite, colour is real, provides perfect display effect

- Flexible way of wearing

Wear comfortable casual. For handheld, his hips and shoulders wear to wear a variety of ways, Overall the characteristics of both the practical and concise design.

- Features

- ◎ IP65 Industrial level material, Ip65
- ◎ power on quickly
- ◎ Main device and camera separation design;
- ◎ Lithium battery power supply
- ◎ GPS ,3G/4G and WIFI function;
- ◎ Working time ≥ 5 hours;
- ◎ A variety of network function, including real-time preview, remote playback, remote download, radio, intercom, message;
- ◎ Support different transport quality.
- ◎ 64G One micro-SD card, support 64G;
- ◎ IP intercom (optional)
- ◎ Support mobile control management platform (optional)

Specification :

Applications :

- Traffic police
- Patrol
- Patrol
- Coastal defense
- Armed police
- Insurance
- Railway
- The courts
- Energy
- Enterprise search
- Interview object



ITEM		DESCRIPTION
Portable Industrial Design		Portable compact host, Select different cameras based on occasions, portable charging by docking station
GUI		Setup system parameters through the Panel controller
Language		Chinese, English, other(optional)
Security		User password management
Video and preview	Video input	Video Compression Criteria
	OSD	Overlays letters... like date & time information and vehicle ID into video streaming
	Video Compression Criteria	H.264.With Hisilicon technology
	Dual stream	Support
	Resolution	Support CIF、HD1、D1
	Video quality	1-4 levels, 1 is the highest level and 4 is the lowest level
	Video Bi	CIF: 400Kbps ~ 1.5Mbps D1: 1000kbps ~ 2Mbps
	Preview	Real time, record video preview
	Audio	Audio Input Audio Output Compression
Record	Storage	Micro-SD card: support 1G~64G
	File Type	H.264 ASF、FAT32
	Recording Mode	Default auto recording after power on, support manual recording
	Video Search	Search video by time , type
	Video playback	Support forward and backward at the speed of: x2, x4, x8, x16, support playback of file by time
LCD parameters	Size	2.4
	Type	TFT
	Resolution	480*234
Wireless transmission		Built-in 3G wireless transmission module, WCDMA, CDMA2000, TD-SCDMA Compatible with GPRS, EDGE; Support up to 4G;(optional) Built-in WIFI

GPS	Built-in GPS or BeiDou;	
Upgrade	Upgrade by SD card or USB	
External Interface	Support data export to USB, Interface charge	
Power & consumption	Power managemen	Manual startup/shutdown; support manual off-screen, automatic off- screen
	Battery capacit	2400mAh , 7.4V
	Chargin g period	< 3 hours
	Workin g	>= 5 hours
Working environment	Operating temperature	-20°C ~ +50°C
	Operating Humidity	10% to 95%
Dimensions	80(W) x140(H) x33(D) mm	

The Diagram Of Attachments :

